B.S. SRL - BADERNE SPECIALI -



VIA G.MARCONI N.11/H 24060 CREDARO (BG)

TEL. E FAX: 035/93.55.54

PACKING SHEET

114 ART. Denomination: Expanded Graphite

TYPE: Very flexible and supple packing, good alternative to pre-formed graphiterings. It combines all the advantages of pure graphite rings with the flexibility, compressibility and ease of installation of a conventional packing; very low coefficient of friction and high thermal conductivity; extended shelf life, does not harden; chemically inert (pH 0-14) except with highly oxidizing agents.

APPLICATIONS: Used for rotary pumps and valves in power stations and boiler houses, in the petrochemical industry and many other industrial areas, with steam, water, fuel, gases, chemicals, mineral and syntetic oils, effluents. Suitable for all processes, except with higly oxidizing media.

NOT SUITABLE FOR: Higly oxidizing agents.

TEMPERATURE	-temp.	+ temp		
(°C)	-240	+450		
PRESSURE	rot.	alt.	stat.	
(BAR)	30	100	300	
STEAM		650		
INERT GAS		1000		
Ph		0 - 14		
DENSITY		1		
SPEEDNESS m/s		20		

B.S. SRL - BADERNE SPECIALI -VIA G.MARCONI N°11/H 24060 CREDARO (BG-)