## B.S. SRL - BADERNE SPECIALI -



VIA G.MARCONI N.11/H 24060 CREDARO (BG)

TEL. E FAX: 035/93.55.54

## **PACKING SHEET**

## 121 ART.

Denomination: PREOX-64

TYPE: Diagonally braided from Preox yarn, impregnated throughout with pure graphte powder and a corrosion inhibitor. It is an economic solution for applications above the temperatue limit of PTFE and gPTFE packings. It fills the gap between the "medium temperature" packings for up to 280°C and the more expensive "high temperature" packings made from pure carbon or graphite. The preox yarn has a low coefficient of friction and excellent heat transmitting properties.

APPLICATIONS: Can be used in pumps, sliders, stirring equipment, refiners and valves in many different industries. Also suitable for boiler feed pumps. it is suitable for use with most chemicals, diluted acids and lyes, water, steam, oil, sovents, brine, sewage, etc.

NOT SUITABLE FOR: Concentrated acids and lyes, oleum, fuming nitric acid.

TEMPERATURE	-temp.	+ temp		
(°C)		+300		
PRESSURE	rot.	alt.	stat.	
(BAR)	25	<u>—</u>	100	
STEAM		_		
INERT GAS		_		
Ph		3 - 12		
DENSITY		0,9		
SPEEDNESS m/s		15		

B.S. SRL - BADERNE SPECIALI -VIA G.MARCONI N°11/H 24060 CREDARO (BG-)