B.S. SRL - BADERNE SPECIALI -



VIA G.MARCONI N.11/H 24060 CREDARO (BG) TEL. E FAX: 035/93.55.54

PACKING SHEET

ART. 200

Denomination: PTFE + PTFE

TYPE: Packing braided from a new type of proprietary yarn made from expanded PTFE with highly refined mineral filler particles. It is a very supple packing with consistently high density and flexibility. Fast and simple to install, with minimum maintenance requirements. Because of the malleability of the unique yarn used for this packing, emissions (leakage) can be adjusted very finely and reduced to extremely low levels. Highest chemical resistance, very low coefficient of friction.

APPLICATIONS: Although primarily designed as a valve packing, can also be used for slow moving rotating equipment like centrifugal pumps and reciprocating pumps, sliders, mixers, etc. The unsurpassed chemical reistance of PTFE makes this packing ideal for nearly all, even the most aggressive, media. Also suitable for pharmaceutical and food applications, potable water, solvents, oils, gases, effluents, etc.

NOT SUITABLE FOR: Molten alkali metals and fluorine compounds at high temperatures and pressures.

| TEMPERATURE | -temp. | + temp | | |
|---------------|--------|--------|-------|--|
| (°C) | - 200 | + 280 | | |
| PRESSURE | rot. | alt. | stat. | |
| (BAR) | 20 | 150 | 250 | |
| STEAM | | _ | | |
| INERT GAS | | _ | | |
| Ph | | 0 - 14 | | |
| DENSITY | | 1,7 | | |
| SPEEDNESS m/s | | 5 | | |

B.S. SRL - BADERNE SPECIALI - VIA G.MARCONI N°11/H 24060 CREDARO (BG)