

B.S. SRL - BADERNE SPECIALI -

VIA G.MARCONI N.11/H 24060 CREDARO (BG) TEL. E FAX: 035/93.55.54

PACKING SHEET

ART. 202

Denomination: PTFE - GN

TYPE: Diagonally braided from pure, expanded PTFE-yarn with incorporated graphite, lubricated with silicone oil. The suppleness, chemical resistance, low coefficient of friction and excellent heat dissipation properties of PTFE/graphite make it one of the most widely used and most versatile packings in the market.

APPLICATIONS: Very versatile pump packing, can also be used for valves, mixers, agitators, etc., particularly well suited for service involving high peripheral speeds and temperatures, where pure PTFE packings fail. Can be safely used for almost all chemical applications including the most aggressive ones.

NOT SUITABLE FOR: Highly oxidizing media like oleum, fuming nitric acid, aqua regia, gaseous fluorine, lacquer and paints.

TEMPERATURE	-temp.	+ tem _l	p	
(°C)	- 200	+ 280		
PRESSURE	rot.	alt.	stat.	
(BAR)	35	100	200	
STEAM	_			
INERT GAS		_		
Ph	0 - 14			
DENSITY	1,6			
SPEEDNESS m/s		25		

B.S. SRL - BADERNE SPECIALI - VIA G.MARCONI N°11/H 24060 CREDARO (BG)