

B.S. SRL - BADERNE SPECIALI -

VIA G.MARCONI N.11/H 24060 CREDARO (BG) TEL. E FAX: 035/93.55.54

PACKING SHEET

ART. 206

Denomination: PTFE FDA

TYPE: Packing braided with expanded Ptfe with filler mineral particles highly refined.

APPLICATIONS: is a very flexible packing with highly density, easy and fast to install; has a very low coefficient of friction and high chemical resistance. Because of the maleability of yarn, emissions can be adjusted very finely and reduced to minimum levels.

Primarily designed as a valve packing, it can be used for slow moving rotating equipment like reciprocating pumps, sliders, mixers etc.

Ideal for pharmaceutical and food applications, potable water, solvents, effluents, etc.

NOT SUITABLE FOR :alkalis metals and fluorine compounds with highly temperature and pressures .

TEMPERATURE	-temp.	+ temp		
(°C)	- 200		+ 280	
PRESSURE	rot.	alt.	stat.	
(BAR)	20	150	250	
STEAM		_		
INERT GAS		_		
Ph	0-14			
DENSITY		1,7		
SPEEDNESS m/s		5		

B.S. SRL - BADERNE SPECIALI - VIA G.MARCONI N°11/H 24060 CREDARO (BG)