

B.S. SRL - BADERNE SPECIALI -

VIA G.MARCONI N.11/H 24060 CREDARO (BG) TEL. E FAX: 035/93.55.54

PACKING SHEET

ART. 211 Denomination: PTFE -G + ARAMIDICO

TYPE: Diagonally braided from gPTFE (PTFE with incorporated graphite), reinforced at the corners with continuous Aramid yarn, lubricated with silicone oil. It is a high performance multi-yarn packing, which combines the advantages of the supple gPTFE material with those of tough and durable Aramid. This results in reduced shaft-wear and better thermal conductivity than standard Aramid packings. APPLICATIONS: Multi-purpose packing, particularly well suited for use in piston-pumps, mixers, stirrers, reactors for industrial and chemical process valves, good for high pressure applications. Can be used with a wide variety of media including abrasive ones: cold and hot water, steam, solvents, oils, greases, diluted acids and lyes, brine, sewage etc.

NOT SUITABLE FOR: Highly concentrated acids and lyes, alkali metals, fluorine and fluorine ocmpounds at highe temperatures.

TEMPERATURE	-temp.	+ tem	p	
(°C)	- 100	+ 280		
PRESSURE	rot.	alt.	stat.	
(BAR)	30	200	200	
STEAM	_			
INERT GAS	_			
Ph		2 - 12		
DENSITY	1,5			
SPEEDNESS m/s		20		

B.S. SRL - BADERNE SPECIALI - VIA G.MARCONI N°11/H 24060 CREDARO (BG)