

B.S. SRL - BADERNE SPECIALI -

VIA G.MARCONI N.11/H 24060 CREDARO (BG) TEL. E FAX: 035/93.55.54

PACKING SHEET

ART. 301

Denomination: ARAMIDICO-L

TYPE: Diagonally braided from continuous Aramid fibres, impregnated with PTFE and high temperature silicone oil. Extremely tough and durable packing with a chemical compatibility better than PTFE-lubricated asbestos and unsurpassed mechanical strength of Aramid. The impregnation with PTFE and lubricant results in a low coefficient of friction.

APPLICATIONS: It is also suited for valves and piston pumps, mixers and reactors in the following industries: pulp and paper, pharmaceutical, food, sugar, chemical and petrochemical, power stations, steel mills, and many more. The chemical resistance of Aramid together with the PTFE- impregnation allows this packing to be used in connection with most chemicals (except very corrosive ones), water, steam, oils, solvents, etc., while its extrem abrasion resistance makes it ideal for use with abrasive sand, slurry and other gritty media.

NOT SUITABLE FOR: Highly concentrated acids, caustic solutions, alkali metals, oxygen.

TEMPERATURE	-temp.	+ temp		
(°C)	- 100	+ 280		
PRESSURE	rot.	alt.	stat.	
(BAR)	35	200	250	
STEAM		_		
INERT GAS	_			
Ph	2 - 12			
DENSITY	1,5			
SPEEDNESS m/s		15		

B.S. SRL - BADERNE SPECIALI - VIA G.MARCONI N°11/H 24060 CREDARO (BG)