

BS**B.S. SRL - BADERNE SPECIALI -**VIA G.MARCONI N.11/H 24060 CREDARO (BG)
TEL. E FAX: 035/93.55.54

PACKING SHEET

ART. 306**Denomination: Aramid with dispersion of Lubricated PTFE**

TYPE: *Diagonally braided from high-grade aramid staple fibre yarn, impregnated throughout with PTFE and a silicone-free lubricant. Very dense packing for high pressure and high speed applications, excellent replacement for PTFE-impregnated asbestos packings, particularly well suited for use with abrasive media.*

APPLICATIONS: *For pumps, valves, sliders, agitators, etc., in most industries where a strong and durable packing is required. Water, steam, oils, lubricants, diluted acids and lyes, abrasive media, paints and varnishes, solvents, gases, etc.*

NOT SUITABLE FOR: *Highly concentrated acids and lyes, a few organic compounds, alkali metals. We recommend a shaft (sleeve) hardness ≥ 60 HRC*

TEMPERATURE	-temp.	+ temp	
(°C)	- 100	+ 280	
PRESSURE	rot.	alt.	stat.
(BAR)	20	80	150
STEAM	—		
INERT GAS	—		
Ph	2 - 12		
DENSITY	1,4		
SPEEDNESS m/s	15		

B.S. SRL - BADERNE SPECIALI -
VIA G.MARCONI N°11/H 24060 CREDARO (BG)