

## B.S. SRL - BADERNE SPECIALI -

VIA G.MARCONI N.11/H 24060 CREDARO ( BG ) TEL. E FAX: 035/93.55.54

## **PACKING SHEET**

*ART.* 402

Denomination: GLASS with PTFE and lubricant

TYPE: Diagonally braided from textured glass-fibre yarn, impregnated throughout with PTFE-dispersion, silicone-free break-in lubricant. Very dense and supple packing, good chemical resistance.

APPLICATIONS: It is recommended for use in rotary and reciprocating pumps, valves, mixers and agitators etc. in the pulp- and paper, petroleum, chemical and food industry, in sugar mills and water treatment plants. It can be used with water, steam, solvents, oils, most chemicals, mild acids and lyes, etc.

NOT SUITABLE FOR: Concentrated acids and lyes, oxygen.

TEMPERATURE	-temp.	+ tem <sub>]</sub>	p
(°C)	-40	+ 280	
PRESSURE	rot.	alt.	stat.
(BAR)	15	20	150
STEAM	_		
INERT GAS	_		
Ph	3,12		
DENSITY	2		
SPEEDNESS m/s	8		

**B.S. SRL** - BADERNE SPECIALI - VIA G.MARCONI N°11/H 24060 CREDARO (BG)