

B.S. SRL - BADERNE SPECIALI -

VIA G.MARCONI N.11/H 24060 CREDARO (BG) TEL. E FAX: 035/93.55.54

PACKING SHEET

ART. 403

Denomination: GLASS with graphite

TYPE: Diagonally braided from high-quality textured glass fibre, impregnated yarn by yarn with pure graphite powder and a corrosion inhititor. The graphiting process reduces fretting of the glass fibre, this prevents the glass fibres form abrading and daamging each other under pressure. It is a dense, yet resilient, packing for static applications.

APPLICATIONS: It is predominantly a valve packing, but can also be recommended for man holes, tank lids and other static applications with water, oils, alkaline solutions, weak acids, chemical products. It is a very strong and durable packing for static applications at high temperatures and pressures.

NOT SUITABLE FOR: Concentrated acids and lyes, steam at temperature above 200°C

TEMPERATURE	-temp.	+ temp	
(°C)	_	+ 550	
PRESSURE	rot.	alt.	stat.
(BAR)	_	_	150
STEAM	200		
INERT GAS		_	
Ph	4,11		
DENSITY	1,5		
SPEEDNESS m/s			

B.S. SRL - BADERNE SPECIALI - VIA G.MARCONI N°11/H 24060 CREDARO (BG)