

## B.S. SRL - BADERNE SPECIALI -

VIA G.MARCONI N.11/H 24060 CREDARO ( BG ) TEL. E FAX: 035/93.55.54

## **PACKING SHEET**

*ART.* 601

**Denomination:** ACRYLIC with teflon and lubricant

TYPE: Diagonally braided from acrylic fibre, impregnated throughout with PTFE-dispersion, lubricated with silicone oil. It is a dense, yet soft and pliable packing. The combination of the synthetic fibres, the PTFE-impregnation and the high-temperature break-in lubricant results in a packing with very low shaft wear and outstanding durability.

APPLICATIONS: This packing can be used in pumps, mixers, kneaders and valves in the chemical, pharmaceutical, pulp and paper and food industry, can be used with water, steam, diluted acids and lyes, most chemicals, gases, etc.

NOT SUITABLE FOR: Concentrated acids and lyes, oxygen, lacquers and paint.

TEMPERATURE	-temp.	+ temp	
(°C)	-100	+ 230	
PRESSURE	rot.	alt.	stat.
(BAR)	20	80	100
STEAM		+ 200	
INERT GAS		_	
Ph		2 - 12	
DENSITY		1,5	
SPEEDNESS m/s		12	

**B.S. SRL** - BADERNE SPECIALI - VIA G.MARCONI N°11/H 24060 CREDARO (BG)